



МАРТ

E-MART
ВАШ ПОСТАВЩИК
DAHUA

<https://emart.su/brands/dahua/>


Федеральный	8 800 511-77-41
Санкт-петербург	8 812 426-99-66
Москва	8 495 137-99-67
Краснодар	8 861 205-62-66

www.emart.su

mail@emart.su

ASI1201E/ASI1201E-D

Water-proof RFID Standalone



Features

- Support 30,000 valid cards & 150,000 records
- Support multiple cards(default IC card) (“-D” means ID EM card)
- Support card, password and combination
- TCP/IP to PC
- Wiegand or RS-485 interface to reader
- Door time out alarm, intrusion alarm, duress alarm and tamper alarm
- Anti-passback, multi-card open
- Water-proof design
- Support 128 efficient time and holiday schedules
- Watch dog function ensure device free from halting



Technical Specification

System

Main Processor	32 Bit
Memory	16M

Input/Output Ports

Input	Door sensor x 1, Exit button x 1
Output	Relay x 1 (Door lock,)
Reader	Reader x 1

Card Read

Read Format	13.56MHz(Mifare)/125KHz(“-D” EM, Optional)
Read Range	3-6cm (max.)
Response Time	<0.1s

Capacity

Cardholders	30,000
Events	150,000

Function

User Management	General, VIP, Guest, Patrol, Black list, Duress
Alarm Function	Door time out alarm, Intrusion alarm, Duress alarm, Tamper alarm
Period Setting	Support 128 groups of schedule, 128 groups of periods and 128 groups of holiday periods


Interface

To PC	RJ45(10/100M)
To Reader	Wiegand/ RS485

General

RTC	Yes
Voice Prompt	No
Beep Tone	Buzzer
Keyboard	Sensitive touch keypad with blue backlight
Power Supply	9-15DC/200mA
Working Environment	-30°C~+60°C
Working Humidity	≤95%
Dimension(W×D×H)	62*23*142mm
Weight	0.5Kg

Dimensions



Application

Small Office
One door controller

